

Outdoor Distributed Energy Storage System (Air-cooling)

Cube72/90/108

- Modular design allows expansion from 4 to 6 modules, offering a capacity range of 72-108kWh, suiting various needs
- Supports 30/40/50kW, catering to small commercial and industrial (C&I) scenarios
- Thermally sensitive wire enables fire extinguishment in extreme conditions, and seamless switching time is $\leq 20\text{ms}$
- Operates with a DC/AC ratio of 1.5 for PV energy, and comes with a 4G/Wifi module for remote access
- Maximizes space utilization by reducing floor space by 55%. Delivered in cabinets, it saves 50% of installation time and cost



Model	Cube 72	Cube 90	Cube 108
System			
Battery Energy (kWh)	72	90	108
Rated Power (kW)	30	40	50
AC Output	400V, 3L+N+PE, 50Hz/60Hz		
Off-Grid Switching Time (ms)	<10		
Communication	Wifi/4G/CAN/RS485		
Cooling Method	Air conditioning cooling		
IP Rating	IP54		
Working Temperature (°C)	Charging: 0~50; Discharging: -20~55; Storage: -20~50		
Humidity	5%RH ~ 95%RH, No condensation		
Altitude (m)	4000 (>2000 derating)		
Dimensions (W*D*H)(mm)	850*900*1650		
Fire Protection System	Aerosol		
Weight (kg)	750	880	1100
Certificates	IEC62619, EN61000, UN38.3		
Battery			
Battery Pack	57.6V/18.08kWh/314Ah		
Battery System (kWh)	72	90	108
Battery Voltage Range (VDC)	201.6~255.6	252.0~319.5	302.4~383.4
Endurance Cycle	8000, 70% SOH (90%DOD, 25°C)		
PV(Optional)			
Max DC Input Power (kW)	38.4k +38.4		
Max DC Input Voltage (VDC)	850		
MPPT Voltage Range (VDC)	200-800		
Start-up Voltage (V)	250		
Max Input Current	64 + 64		
AC Side			
Rated Output Active Power (kW)	30	40	50
Max Output Current(A)	47.9	63.8	79.8
THDi	<3% (Over 30% load)		
THDu	<3% (Resistive load)		
PCS Certificates	CE, IEC62019, IEC62477, IEC6100, EN50549		

Shenzhen Ruidian Green Energy Technology Co.,Ltd

Office Address: A801 Building 3A, Cloud Park, Bantian, Longgang District, Shenzhen
 Factory Address: No.3, East Hua'n'an Road, Dongjiang Hi-Tech Industrial Park, Huizhou

4008-036-037

www.absenenergy.com

